

**UK Patent Application** **GB** **2 265 935** **A**

(19) Date of A publication 13.10.1983

(21) Application No 8227100.0

(22) Date of filing 01.04.1992

(71) Applicant  
Cargo Limited

(Incorporated in the United Kingdom)  
Western Road, Silver End, Willham, Essex, CM8 3QB,  
United Kingdom

(72) Inventors  
Melvin John Hutton  
John Kelly

(74) Agent and/or Address for Service  
Mathiesen Masera & Co  
The Coach House, 6-8 Snares Lane, Ickenham,  
Uxbridge, Middlesex, UB10 8RZ, United Kingdom

(51) INT CL<sup>6</sup>  
E05C 9/04


(52) UK CL (Edition L)  
E2A AMX A16D A16Z A42D A42I A50B

(56) Documents cited  
GB 2089588 A GB 0850193 A US 4142747 A

(58) Field of search  
UK CL (Edition L) E2A AAK AMX  
INT CL<sup>6</sup> E05C 9/00 9/02 9/04 9/06  
Online database: WPI

**(54) Espagnolette type mechanism**

(57) An operating mechanism (3) for a door or window fastener in which two slidably mounted locking bars (1, 2) are driven by the operating mechanism simultaneously in opposite directions to fasten or unfasten the door or window comprises a drive member (21) driven by the spindle of an operating handle and a pair of linearly guided reciprocable slide plates (13, 14) which are connected to the drive member (21) by pin and slot connections (28, 23a) and (27, 24a) at diametrically opposite positions with respect to the axis of rotation of the drive member so that the two slide plates move linearly in opposite directions. The fastener may be of the espagnolette type and/or the locking bars (1, 2) may be arranged to operate pivoted head shaped locking members (42).



*Fig.1.*

At least one drawing originally filed was informal and the print reproduced here is taken from a later filed formal copy.

The claims were filed later than the filing date within the period prescribed by Rule 25(1) of the Patents Rules 1990.

**GB 2 265 935 A**